

# Product data sheet

## Characteristics


# 8736SDO2V02S

NEMA Starter, Type S, reversing, horizontal, Size 2, 45A, 25 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 2349.00 USD



### Main

Product or component type	Starter
Range of product	S
Motor starter type	Reversing

### Complementary

NEMA size	2
Line Rated Current	45 A
Poles description	3P
Installation direction	Horizontal
Wiring mode	3 wires
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control units	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical connection	Screw clamp terminals
Height	8.50 In (215.90 mm)
Width	9.00 In (228.60 mm)
Depth	6.03 In (153.16 mm)

## Environment

NEMA degree of protection	Not rated (open device)
Product certifications	UL Listed CSA


## Ordering and shipping details

Category	21272 - 8702,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901884330
Nbr. of units in pkg.	1
Package weight(Lbs)	15.81 Lb(US) (7.171 kg)
Returnability	No
Country of origin	MX

## Packing Units

Package 1 Height	8.50 In (21.590 cm)
Package 1 width	11.30 In (28.702 cm)
Package 1 Length	14.00 In (35.560 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**