

Product data sheet

Characteristics

8736SEO1V02S

NEMA Starter, Type S, reversing, vertical, Size 3, 90A, 50 HP at 575 VAC, 5 kA SSCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 3902.00 USD



Main

Product or component type	Starter
Range of product	S
Motor starter type	Reversing

Complementary

NEMA size	3
Line Rated Current	90 A
Poles description	3P
Installation direction	Vertical
Wiring mode	3 wires
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	25 HP 200 V AC 30 HP 230 V AC 50 HP 460 V AC 50 HP 575 V AC
Product compatibility	Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control units	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical connection	Screw clamp terminals
Height	22.25 In (565.15 mm)
Width	7.31 In (185.67 mm)
Depth	7.00 In (177.80 mm)


Environment

NEMA degree of protection	Not rated (open device)
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21273 - 8702,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901021780
Nbr. of units in pkg.	1
Package weight(Lbs)	35.02 Lb(US) (15.885 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**