

Product data sheet

Characteristics

8736SGO1V02S

NEMA Starter, Type S, reversing, vertical, Size 5, 270A, 200 HP at 575 VAC, 10 kA SCCR, 3 phase, 3 pole, melting alloy overload, 120 VAC coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product or component type	Starter
Range of product	S
Motor starter type	Reversing

Complementary

NEMA size	5
Line Rated Current	270 A
Poles description	3P
Installation direction	Vertical
Wiring mode	3 wires
[Ue] rated operational voltage	600 V AC
Phase	3 phase
Thermal overload type	Melting alloy 3
Rated power in HP	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC
Product compatibility	Circuit-breaker: 10 kA at 600 V AC Fuse: 10 kA at 600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Control circuit	Separate control circuit
Control units	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Electrical connection	Screw clamp terminals
Height	39.16 In (994.66 mm)
Width	10.75 In (273.05 mm)
Depth	9.38 In (238.25 mm)


Environment

NEMA degree of protection	Not rated (open device)
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21274 - 8702,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	00785901865469
Nbr. of units in pkg.	1
Package weight(Lbs)	110.00 Lb(US) (49.895 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**