

Product data sheet

Characteristics

8903LO20V02

Contactor, Type L, multipole lighting, electrically held, 30A, 2 pole, 600 V, 110/120 VAC 50/60 Hz coil, open style



Product availability: Stock - Normally stocked in distribution facility

Price*: 404.00 USD



Main

| | |
|---------------------------|--------------------------------------|
| Product or Component Type | Electrically Held Lighting Contactor |
| Range of Product | 8903L |
| Control circuit | Separate control circuit |

Complementary

| | |
|---------------------------------|-----------------------------------|
| [Uc] control circuit voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Inrush power in VA | 150 VA 60 Hz 140 VA 50 Hz |
| Hold-in power consumption in VA | 30 VA 60 Hz 30 VA 50 Hz |
| Line Rated Current | 20 A tungsten 30 A fluorescent |
| Poles description | 2P 2 NO |
| Control type | No control units |
| Local signalling | No indicator |
| Electrical Connection | Screw-clamp terminals |
| Maximum Height | 5.00 In (127 mm) |
| Maximum Depth | 3.11 In (79 mm) |
| Maximum Width | 2.87 In (73 mm) |

Environment

| | |
|---------------------------|-------------------------|
| NEMA degree of protection | Not rated (open device) |
| Product Certifications | UL Listed CSA |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to determine the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. *Prices are indicative.

Ordering and shipping details

| | |
|-----------------------|-------------------------|
| Category | 21321 - 8903 L (NOT LX) |
| Discount Schedule | CP1 |
| GTIN | 00785901851639 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.80 Lb(US) (1.27 kg) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 4.49 In (11.4 cm) |
| Package 1 width | 6.18 In (15.7 cm) |
| Package 1 Length | 7.01 In (17.8 cm) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**