

# Product data sheet

## Characteristics

# 8903LO30V04

Contacteur, Type L, multipole lighting, electrically held, 30A, 3 pole, 600 V, 277 VAC 60 Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 446.00 USD



### Main

Product or Component Type	Electrically Held Lighting Contactor
Range of Product	8903L
Control circuit	Separate control circuit

### Complementary

[Uc] control circuit voltage	277 V AC 60 Hz
Inrush power in VA	150 VA 60 Hz
Hold-in power consumption in VA	30 VA 60 Hz
Line Rated Current	20 A tungsten 30 A fluorescent
Poles description	3P 3 NO
Control type	No control units
Local signalling	No indicator
Electrical Connection	Screw-clamp terminals
Maximum Height	5.00 In (127 mm)
Maximum Depth	3.11 In (79 mm)
Maximum Width	2.87 In (73 mm)

### Environment

NEMA degree of protection	Not rated (open device)
Product Certifications	UL Listed CSA

### Ordering and shipping details

Category	21321 - 8903 L (NOT LX)
Discount Schedule	CP1
GTIN	00785901459231
Nbr. of units in pkg.	1
Package weight(Lbs)	2.79 Lb(US) (1.27 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	4.40 In (11.176 cm)
Package 1 width	6.20 In (15.748 cm)
Package 1 Length	6.80 In (17.272 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**