

Product data sheet

Characteristics

8903LXG1000V02

Contactor, Type LX multipole lighting,
mechanically held, 30A, 10 pole, 600 V, 110/120
VAC 50/60 Hz coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1430.00 USD



Main

Product or Component Type	Mechanically Held Lighting Contactor
Range of Product	8903LX
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Inrush power in VA	180 VA 60 Hz 170 VA 50 Hz 25 VA 50/60 Hz
Line Rated Current	20 A tungsten 30 A fluorescent
Poles description	10P 10 NO
Control type	No control units
Local signalling	No indicator
Additional included device	None
Electrical Connection	Screw-clamp terminals
Maximum Height	12.68 In (322 mm)
Maximum Depth	6.02 In (153 mm)
Maximum Width	7.80 In (198 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel surface
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21322 - 8903 LX (NOT L)
Discount Schedule	CP1
GTIN	00785901057444
Nbr. of units in pkg.	1
Package weight(Lbs)	12.18 Lb(US) (5.52 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	7.70 In (19.558 cm)
Package 1 width	8.30 In (21.082 cm)
Package 1 Length	13.00 In (33.020 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	----------------