

Product data sheet

Characteristics

8903LXO40V06

8903LX mechanically held lighting contactor, 4 P, 4 NO, 30 A, 600 V, 440/480 V 50/60 Hz coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility



Main

| | |
|---------------------------|--------------------------------------|
| Product or Component Type | Mechanically Held Lighting Contactor |
| Range of Product | 8903LX |
| Control circuit | Separate control circuit |

Complementary

| | |
|------------------------------|--|
| [Uc] control circuit voltage | 440 V AC 50 Hz 480 V AC 60 Hz |
| Inrush power in VA | 150 VA 60 Hz 140 VA 50 Hz 25 VA 50/60 Hz |
| Line Rated Current | 20 A tungsten 30 A fluorescent |
| Poles description | 4P 4 NO |
| Control type | No control units |
| Local signalling | No indicator |
| Additional included device | None |
| Electrical Connection | Screw-clamp terminals |
| Maximum Height | 8.82 In (224 mm) |
| Maximum Depth | 3.27 In (83 mm) |
| Maximum Width | 2.87 In (73 mm) |

Environment

| | |
|---------------------------|-------------------------|
| NEMA degree of protection | Not rated (open device) |
| Product Certifications | UL Listed CSA |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|-----------------------|-------------------------|
| Category | 21322 - 8903 LX (NOT L) |
| Discount Schedule | CP1 |
| GTIN | 00785901504245 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 8.71 Lb(US) (3.952 kg) |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 4.00 In (10.16 cm) |
| Package 1 width | 7.50 In (19.05 cm) |
| Package 1 Length | 10.50 In (26.67 cm) |

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**