

Product data sheet

Characteristics


8903LXO60V04

8903LX mechanically held lighting contactor, 6 P,
6 NO, 30 A, 600 V, 277 V 60 Hz coil, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1044.00 USD



Main

Product or Component Type	Mechanically Held Lighting Contactor
Range of Product	8903LX
Control circuit	Separate control circuit

Complementary

[Uc] control circuit voltage	277 V AC 60 Hz
Inrush power in VA	180 VA 60 Hz 25 VA 50/60 Hz
Line Rated Current	20 A tungsten 30 A fluorescent
Poles description	6P 6 NO
Control type	No control units
Local signalling	No indicator
Additional included device	None
Electrical Connection	Screw-clamp terminals
Maximum Height	8.82 In (224 mm)
Maximum Depth	3.27 In (83 mm)
Maximum Width	4.25 In (108 mm)

Environment

NEMA degree of protection	Not rated (open device)
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	21322 - 8903 LX (NOT L)
Discount Schedule	CP1
GTIN	00785901057376
Nbr. of units in pkg.	1
Package weight(Lbs)	5.05 Lb(US) (2.291 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.50 In (11.43 cm)
Package 1 width	7.20 In (18.288 cm)
Package 1 Length	10.50 In (26.67 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**