

Product data sheet

Characteristics

8903SMG2V03

Contacteur, Type S, multipole lighting, electrically held, 30A, 3 pole, 220/240 VAC 50/60 Hz coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 518.00 USD



Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	240 V AC 60 Hz 220 V AC 50 Hz
Line Rated Current	30 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	10.00 In (254 mm)
Depth	5.28 In (134 mm)
Width	5.98 In (152 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901619550
Nbr. of units in pkg.	1
Package weight(Lbs)	6.32 Lb(US) (2.867 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.30 In (16.002 cm)
Package 1 width	6.50 In (16.51 cm)
Package 1 Length	10.60 In (26.924 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**