

# Product data sheet

## Characteristics

# 8903SMO2V02

Contactor, Type S, multipole lighting, electrically held, 30A, 3 pole, 110/120 VAC 50/60 Hz coil, open style



Product availability: Stock - Normally stocked in distribution facility

Price\*: 489.00 USD



### Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	30 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	3.50 In (89 mm)
Depth	4.21 In (107 mm)
Width	3.23 In (82 mm)

### Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901619529
Nbr. of units in pkg.	1
Package weight(Lbs)	3.13 Lb(US) (1.42 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.61 In (11.7 cm)
Package 1 width	5.91 In (15 cm)
Package 1 Length	8.11 In (20.6 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**