

Product data sheet

Characteristics

8903SPG11V02

Contactor, Type S, multipole lighting,
mechanically held, 60A, 3 pole, 110/120VAC
50/60Hz coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1544.00 USD



Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	60 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	14.13 In (359 mm)
Depth	9.72 In (247 mm)
Width	8.11 In (206 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901102595
Nbr. of units in pkg.	1
Package weight(Lbs)	20.18 Lb(US) (9.15 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	10.80 In (27.432 cm)
Package 1 width	10.50 In (26.670 cm)
Package 1 Length	16.70 In (42.418 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**