

# Product data sheet

## Characteristics

# 8903SPO11V02

Contactor, Type S, multipole lighting,  
mechanically held, 60A, 3 pole, 110/120 VAC  
50/60 Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1430.00 USD



### Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	60 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	7.80 In (198 mm)
Depth	5.24 In (133 mm)
Width	4.61 In (117 mm)

### Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901102489
Nbr. of units in pkg.	1
Package weight(Lbs)	8.8 Lb(US) (3.99 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	8.40 In (21.336 cm)
Package 1 width	8.30 In (21.082 cm)
Package 1 Length	12.20 In (30.988 cm)

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**