

# Product data sheet

## Characteristics

# 8903SPO1V02

Contactor, Type S, multipole lighting, electrically held, 60A, 2 pole, 110/120 VAC 50/60 Hz coil, open style



Product availability: Stock - Normally stocked in distribution facility

Price\*: 831.00 USD



### Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	60 A
Poles description	2P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	5.51 In (140 mm)
Depth	4.92 In (125 mm)
Width	4.33 In (110 mm)

### Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein. \*Prices are indicative

### Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901619468
Nbr. of units in pkg.	1
Package weight(Lbs)	5.40 Lb(US) (2.449 kg)
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.90 In (17.526 cm)
Package 1 width	6.50 In (16.51 cm)
Package 1 Length	9.30 In (23.622 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**