

Product data sheet

Characteristics

8903SPO2V04

Contactor, Type S, multipole lighting, electrically held, 60A, 3 pole, 277VAC 60Hz coil, open style



Price*: 890.00 USD



Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	277 V AC 60 Hz
Line Rated Current	60 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	5.51 In (140 mm)
Depth	4.92 In (125 mm)
Width	4.33 In (110 mm)

Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325-8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901823445
Package weight(Lbs)	5.53 Lb(US) (2.508 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	7.10 In (18.034 cm)
Package 1 width	6.50 In (16.510 cm)
Package 1 Length	9.30 In (23.622 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------