

Product data sheet

Characteristics

8903SQG2V02

Contactor, Type S, multipole lighting, electrically held, 100A, 3 pole, 110/120 VAC 50/60 Hz coil, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price*: 1715.00 USD



Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	100 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	25.16 In (639 mm)
Depth	8.98 In (228 mm)
Width	11.26 In (286 mm)

Environment

NEMA degree of protection	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901619437
Nbr. of units in pkg.	1
Package weight(Lbs)	34.48 Lb(US) (15.64 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.91 In (27.7 cm)
Package 1 width	11.89 In (30.2 cm)
Package 1 Length	25.51 In (64.8 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**