

Product data sheet

Characteristics

8903SQO10V02

Contactor, Type S, multipole lighting, mechanically held, 100A, 2 pole, 110/120 V 50/60 Hz coil, 600 VAC, open



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1827.00 USD



Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	100 A
Poles description	2P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	7.24 ln (184 mm)
Depth	6.73 ln (171 mm)
Width	5.94 ln (151 mm)

Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901861980
Nbr. of units in pkg.	1
Package weight(Lbs)	17.88 Lb(US) (8.11 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	9.50 In (24.130 cm)
Package 1 width	13.80 In (35.052 cm)
Package 1 Length	18.00 In (45.720 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**