

# Product data sheet

## Characteristics

# 8903SQO11V02

Contactor, Type S, multipole lighting,  
mechanically held, 100A, 3 pole, 110/120 VAC  
50/60 Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1943.00 USD



### Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	100 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	7.24 In (184 mm)
Depth	6.73 In (171 mm)
Width	5.94 In (151 mm)

### Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901102427
Nbr. of units in pkg.	1
Package weight(Lbs)	18.15 Lb(US) (8.23 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	9.60 In (24.384 cm)
Package 1 width	13.70 In (34.798 cm)
Package 1 Length	17.80 In (45.212 cm)

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**