

# Product data sheet

## Characteristics

# 8903SVG11V02

Contactor, Type S, multipole lighting,  
mechanically held, 200A, 3 pole, 110/120VAC  
50/60Hz coil, NEMA 1



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 6015.00 USD



### Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	200 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	39.13 In (994 mm)
Depth	10.24 In (260 mm)
Width	22.17 In (563 mm)

### Environment

NEMA degree of protection	NEMA 1 painted sheet steel surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901102564
Nbr. of units in pkg.	1
Package weight(Lbs)	105 Lb(US) (47.63 kg)
Returnability	No
Country of origin	MX

### Packing Units

Package 1 Height	0.98 Ft (0.300 m)
Package 1 width	2.11 Ft (0.643 m)
Package 1 Length	3.65 Ft (1.113 m)

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**