

Product data sheet

Characteristics

8903SVO11V02

Contactor, Type S, multipole lighting,
mechanically held, 200A, 3 pole, 110/120VAC
50/60Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 4877.00 USD



Main

Product or component type	Mechanically Held Lighting Contactor
Range of product	S

Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	200 A
Poles description	3P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	9.13 In (232 mm)
Depth	6.73 In (171 mm)
Width	5.98 In (152 mm)

Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901102502
Nbr. of units in pkg.	1
Package weight(Lbs)	23.33 Lb(US) (10.582 kg)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	9.70 In (24.638 cm)
Package 1 width	13.70 In (34.798 cm)
Package 1 Length	17.80 In (45.212 cm)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**