

# Product data sheet

## Characteristics

# 8903SVO1V02

Contactor, Type S, multipole lighting, electrically held, 200A, 2 pole, 110/120VAC 50/60Hz coil, open style



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 3167.00 USD



### Main

Product or component type	Electrically Held Lighting Contactor
Range of product	S

### Complementary

[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	200 A
Poles description	2P
Control type	No control units
Local signalling	Without pilot light
Auxiliary contact composition	Without
Additional included device	None
Electrical connection	Lugs
Height	9.13 In (232 mm)
Depth	6.50 In (165 mm)
Width	5.98 In (152 mm)

### Environment

NEMA degree of protection	Not rated (open device) surface none
Product certifications	UL Listed CSA

### Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901626015
Nbr. of units in pkg.	1
Package weight(Lbs)	17.00 Lb(US) (7.711 kg)
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.80 In (19.812 cm)
Package 1 width	8.80 In (22.352 cm)
Package 1 Length	14.40 In (36.576 cm)

### Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**