

Product data sheet

Characteristics

8910DP12V14

Contactor, Definite Purpose, 20A, 2 pole, 24/24 VAC 50/60 Hz coil, open



Product availability: Stock - Normally stocked in distribution facility

Price*: 49.13 USD



Commercial status

This Product is Obsolete : JUL 09, 2021

⚠ This Product is Obsolete

Main

Product or component type	Definite Purpose Contactor
Line Rated Current	20 A
Poles description	2P
Pole contact composition	2 NO
Range of product	DP

Complementary

Maximum Horse Power Rating	1 Hp 115 V AC, 1 phase 2 Hp 230 V AC, 1 phase
Locked rotor rated current	100 A 460 V AC 80 A 575 V AC 120 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	24 V AC 50/60 Hz
Phase	1 phase
Electrical connection	Quick connect terminals Binder head

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21352 - 8910 DP 12
Discount Schedule	CP1B
GTIN	00785901080466
Nbr. of units in pkg.	1
Package weight(Lbs)	1 Lb(US) (0.45 kg)

Aug 19, 2021

Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.30 In (5.842 cm)
Package 1 width	3.40 In (8.636 cm)
Package 1 Length	2.60 In (6.604 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	12
Package 2 Weight	7.47 Lb(US) (3.388 kg)
Package 2 Height	5.80 In (14.732 cm)
Package 2 width	7.00 In (17.78 cm)
Package 2 Length	7.30 In (18.542 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **End of commerc. - Block**

8910DP12V14 may be replaced by any of the following products:



8910DP32V14

Contacteur, Definite Purpose, 30A, 2 pole, 24/24 VAC 50/60 Hz coil, open

Qty 1

Substitution date: |