

# Product data sheet

## Characteristics

# 8910DPA33V02Y122

Contactor, Definite Purpose, 30A, 3 pole, 20 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, pressure wire connector



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 127.04 USD



### Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Poles description	3P
Pole contact composition	3 NO
Range of product	DPA

### Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 Hp 575 V AC, 3 phase
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical connection	Pressure wire clamp Binder head

### Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

### Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)
Discount Schedule	CP1B
GTIN	00785901316978
Nbr. of units in pkg.	1
Package weight(Lbs)	16.00 Oz (453.592 g)
Returnability	No
Country of origin	CN

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.30 In (8.382 cm)
Package 1 width	4.00 In (10.16 cm)
Package 1 Length	2.50 In (6.35 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

### Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**