

Product data sheet

Characteristics

8910DPA34V02U1

Contacteur, Definite Purpose, 30A, 4 pole, 20 HP at 575 VAC, 3 phase, 110/120 VAC 50/60 Hz coil, open, UL Listed



Product availability: Stock - Normally stocked in distribution facility

Price*: 127.50 USD



Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Poles description	4P
Pole contact composition	4 NO
Range of product	DPA

Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 Hp 575 V AC, 3 phase
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	3 phase
Electrical connection	Binder head

Environment

Product certifications	UL Listed CSA
------------------------	------------------

Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)
Discount Schedule	CP1B
GTIN	00785901159834
Nbr. of units in pkg.	1
Package weight(Lbs)	1.27 Lb(US) (0.58 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Package 1 Height	3.30 In (8.382 cm)
Package 1 width	3.30 In (8.382 cm)
Package 1 Length	4.20 In (10.668 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**