

Product data sheet

Characteristics


8910DPA34V04

Contactor, Definite Purpose, 30A, 4 pole, 20 HP at 575 VAC, 3 phase, 277 VAC 60 Hz coil, open



Product availability: Stock - Normally stocked in distribution facility

Price*: 127.50 USD



Main

Product or component type	Definite Purpose Contactor
Line Rated Current	30 A
Poles description	4P
Pole contact composition	4 NO
Range of product	DPA

Complementary

Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase 10 Hp 230 V AC, 3 phase 15 Hp 460 V AC, 3 phase 20 Hp 575 V AC, 3 phase
Locked rotor rated current	150 A 460 V AC 120 A 575 V AC 180 A 277 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	277 V AC 60 Hz
Phase	3 phase
Electrical connection	Quick connect terminals Binder head

Environment

Product certifications	UL Recognized CSA
------------------------	----------------------

Ordering and shipping details

Category	21343 - 8910 DPA 3_(30 AMP)
Discount Schedule	CP1B
GTIN	00785901024439
Nbr. of units in pkg.	1
Package weight(Lbs)	19.84 Oz (562.455 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.20 In (8.128 cm)
Package 1 width	3.30 In (8.382 cm)
Package 1 Length	4.10 In (10.414 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**