

Product data sheet

Characteristics

8911DPSG13V06

Starter, Definite Purpose, nonreversing, 20A, 3 pole, 3 phase, 440/480VAC 50/60Hz coil, melting alloy overload, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price*: 385.04 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	20 A
Maximum Horse Power Rating	3 Hp 230 V AC, 1 phase 7.5 Hp 230 V AC, 3 phase 1.5 Hp 115 V AC, 1 phase 7.5 Hp 460 V AC, 3 phase 7.5 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase

Complementary

Enclosure Material	Painted sheet steel
NEMA Degree of Protection	NEMA 1
Locked rotor rated current	120 A 230 V AC 100 A 460 V AC 80 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901024637
Nbr. of units in pkg.	1
Package weight(Lbs)	5.60 Lb(US) (2.54 kg)

Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.30 In (18.542 cm)
Package 1 width	8.60 In (21.844 cm)
Package 1 Length	13.30 In (33.782 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State-of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**