

## Product data sheet

### Characteristics

# 8911DPSG13V09

Starter, Definite Purpose, nonreversing, 20A, 3 pole, 3 phase, 208 to 240 VAC coil, melting alloy overload, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price\*: 385.04 USD



### Main

|                                |                                                                                                                                        |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| Product or Component Type      | Definite Purpose Starter                                                                                                               |
| Line Rated Current             | 20 A                                                                                                                                   |
| Maximum Horse Power Rating     | 3 Hp 230 V AC, 1 phase<br>7.5 Hp 230 V AC, 3 phase<br>1.5 Hp 115 V AC, 1 phase<br>7.5 Hp 460 V AC, 3 phase<br>7.5 Hp 575 V AC, 3 phase |
| [Ue] rated operational voltage | 600 V AC                                                                                                                               |
| [Uc] control circuit voltage   | 220 V AC 50 Hz<br>208...240 V AC 60 Hz                                                                                                 |
| Phase                          | 3 phase                                                                                                                                |

### Complementary

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| Enclosure Material               | Painted sheet steel                               |
| NEMA Degree of Protection        | NEMA 1                                            |
| Locked rotor rated current       | 120 A 230 V AC<br>100 A 460 V AC<br>80 A 575 V AC |
| Poles description                | 3P                                                |
| Range of Product                 | DPS                                               |
| Thermal overload type            | Melting alloy                                     |
| Number of thermal units required | 3                                                 |

### Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 21381 - 8911 DP        |
| Discount Schedule     | CP1                    |
| GTIN                  | 00785901024644         |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 5.69 Lb(US) (2.581 kg) |

|                   |     |
|-------------------|-----|
| Returnability     | Yes |
| Country of origin | CN  |

**Packing Units**

|                        |                      |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE                  |
| Package 1 Height       | 6.40 In (16.256 cm)  |
| Package 1 width        | 6.90 In (17.526 cm)  |
| Package 1 Length       | 11.20 In (28.448 cm) |

**Offer Sustainability**

|                            |                                               |
|----------------------------|-----------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                           |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |

**Contractual warranty**

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

|                       |                       |
|-----------------------|-----------------------|
| Product Life Status : | <b>Commercialised</b> |
|-----------------------|-----------------------|