

Product data sheet

Characteristics

8911DPSG42V02

Starter, Definite Purpose, nonreversing, 40A, 2 pole, 1 phase, 120 VAC coil, melting alloy overload, NEMA 1, +options



Product availability: Stock - Normally stocked in distribution facility

Price*: 460.74 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	40 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 7.5 Hp 230 V AC, 1 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	1 phase

Complementary

Enclosure Material	Painted sheet steel
NEMA Degree of Protection	NEMA 1
Locked rotor rated current	240 A 230 V AC 200 A 460 V AC 160 A 575 V AC
Poles description	2P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	1

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901001515
Nbr. of units in pkg.	1
Package weight(Lbs)	5.66 Lb(US) (2.567 kg)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.70 In (17.018 cm)
Package 1 width	7.00 In (17.78 cm)
Package 1 Length	11.40 In (28.956 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**