

# Product data sheet

## Characteristics

8911DPSG42V09

Starter, Definite Purpose, nonreversing, 40A, 2 pole, 1 phase, 208 to 240VAC coil, melting alloy overload, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price\*: 460.74 USD



### Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	40 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 7.5 Hp 230 V AC, 1 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	1 phase

### Complementary

Enclosure Material	Painted sheet steel
NEMA Degree of Protection	NEMA 1
Locked rotor rated current	240 A 230 V AC 200 A 460 V AC 160 A 575 V AC
Poles description	2P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	1

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901724766
Nbr. of units in pkg.	1
Package weight(Lbs)	5.83 Lb(US) (2.644 kg)
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.50 In (16.51 cm)
Package 1 width	7.00 In (17.78 cm)
Package 1 Length	11.30 In (28.702 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State-of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**