

# Product data sheet

## Characteristics

# 8911DPSG43V06

Starter, Definite Purpose, nonreversing, 40A, 3 pole, 3 phase, 480 VAC coil, melting alloy overload, NEMA 1, +options



Product availability: Stock - Normally stocked in distribution facility

Price\*: 496.44 USD



### Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	40 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 3 phase 7.5 Hp 230 V AC, 1 phase 20 Hp 460 V AC, 3 phase 25 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase

### Complementary

Enclosure Material	Painted sheet steel
NEMA Degree of Protection	NEMA 1
Locked rotor rated current	240 A 230 V AC 200 A 460 V AC 160 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901024705
Nbr. of units in pkg.	1
Package weight(Lbs)	5.70 Lb(US) (2.586 kg)

Returnability	Yes
Country of origin	CN

**Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	6.30 In (16.002 cm)
Package 1 width	7.00 In (17.78 cm)
Package 1 Length	10.80 In (27.432 cm)

**Offer Sustainability**

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

**Contractual warranty**

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**