

Product data sheet

Characteristics

8911DPSG53V06

Starter, Definite Purpose, nonreversing, 50A, 3 pole, 3 phase, 440/480VAC 50/60Hz coil, melting alloy overload, NEMA 1



Product availability: Stock - Normally stocked in distribution facility

Price*: 752.75 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	50 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	440 V AC 50 Hz 480 V AC 60 Hz
Phase	3 phase

Complementary

Enclosure Material	Painted sheet steel
NEMA Degree of Protection	NEMA 1
Locked rotor rated current	300 A 230 V AC 250 A 460 V AC 200 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901025092
Nbr. of units in pkg.	1
Package weight(Lbs)	9.73 Lb(US) (4.414 kg)

Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.40 In (18.796 cm)
Package 1 width	8.70 In (22.098 cm)
Package 1 Length	13.50 In (34.29 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------