

Product data sheet

Characteristics


8911DPSO13V09

Starter, Definite Purpose, nonreversing, 20A, 3 pole, 3 phase, 208 to 240VAC coil, melting alloy overload, open style



Product availability: Stock - Normally stocked in distribution facility

Price*: 321.20 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	20 A
Maximum Horse Power Rating	3 Hp 230 V AC, 1 phase 7.5 Hp 230 V AC, 3 phase 1.5 Hp 115 V AC, 1 phase 7.5 Hp 460 V AC, 3 phase 7.5 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	3 phase

Complementary

NEMA Degree of Protection	Not rated (open device)
Locked rotor rated current	120 A 230 V AC 100 A 460 V AC 80 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901025146
Nbr. of units in pkg.	1
Package weight(Lbs)	2.30 Lb(US) (1.043 kg)

Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.00 In (12.7 cm)
Package 1 width	5.10 In (12.954 cm)
Package 1 Length	8.20 In (20.828 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals which are known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status :	Commercialised
-----------------------	-----------------------