

# Product data sheet

## Characteristics

# 8911DPSO23V06

## STARTER 600VAC 25AMP DPS +OPTIONS

Product availability: Stock - Normally stocked in distribution facility

Price\*: 320.00 USD



### Main

Commercial Status	Commercialised
Product or component type	Definite Purpose Starter
Line Rated Current	25 A
Motor power hp	20 hp 575 V AC 3 phases 15 hp 460 V AC 3 phases 10 hp 230 V AC 3 phases 5 hp 230 V AC 1 phase 2 hp 115 V AC 1 phase
System Voltage	600 V AC
Control circuit voltage	480 V AC 60 Hz 440 V AC 50 Hz
Phase	3 phases

### Complementary

NEMA degree of protection	Not rated (open device)
Locked rotor rated current	100 A 575 V AC 125 A 460 V AC 150 A 230 V AC
Poles description	3P
Range of product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901556695
Nbr. of units in pkg.	1
Product availability	Stock - Normally stocked in distribution facility
Returnability	Y
Country of origin	CN

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant
REACH	Reference not containing SVHC above the threshold

### Contractual warranty

Warranty period	18 months
-----------------	-----------