

Product data sheet

Characteristics


8911DPSO32V09

Starter, Definite Purpose, nonreversing, 30A, 2 pole, 1 phase, 208 to 240 VAC coil, melting alloy overload, open style



Product availability: Stock - Normally stocked in distribution facility

Price*: 360.15 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	30 A
Maximum Horse Power Rating	2 Hp 115 V AC, 1 phase 5 Hp 230 V AC, 1 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	1 phase

Complementary

NEMA Degree of Protection	Not rated (open device)
Locked rotor rated current	180 A 230 V AC 150 A 460 V AC 120 A 575 V AC
Poles description	2P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	1

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901025160
Nbr. of units in pkg.	1
Package weight(Lbs)	35.20 Oz (997.903 g)
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.80 In (12.192 cm)
Package 1 width	4.70 In (11.938 cm)
Package 1 Length	7.90 In (20.066 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**