

# Product data sheet

## Characteristics

# 8911DPSO43V02

Starter, Definite Purpose, nonreversing, 40A,  
3 pole, 3 phase, 120 VAC coil, melting alloy  
overload, open style



Product availability: Stock - Normally stocked in distribution facility

Price\*: 431.55 USD



### Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	40 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 3 phase 7.5 Hp 230 V AC, 1 phase 20 Hp 460 V AC, 3 phase 25 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase

### Complementary

NEMA Degree of Protection	Not rated (open device)
Locked rotor rated current	240 A 230 V AC 200 A 460 V AC 160 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

### Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901856368
Nbr. of units in pkg.	1
Package weight(Lbs)	2.31 Lb(US) (1.048 kg)

Returnability	Yes
Country of origin	CN

**Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	5.10 In (12.954 cm)
Package 1 width	4.90 In (12.446 cm)
Package 1 Length	7.90 In (20.066 cm)

**Offer Sustainability**

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

**Contractual warranty**

Warranty	18 months
----------	-----------

Product Life Status :	<b>Commercialised</b>
-----------------------	-----------------------