

Product data sheet

Characteristics

8911DPSO53V02

Starter, Definite Purpose, nonreversing, 50A,
3 pole, 3 phase, 120 VAC coil, melting alloy
overload, open style



Product availability: Stock - Normally stocked in distribution facility

Price*: 689.96 USD



Main

Product or Component Type	Definite Purpose Starter
Line Rated Current	50 A
Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 Hp 230 V AC, 1 phase 15 Hp 230 V AC, 3 phase 30 Hp 460 V AC, 3 phase 30 Hp 575 V AC, 3 phase
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase

Complementary

NEMA Degree of Protection	Not rated (open device)
Locked rotor rated current	300 A 230 V AC 250 A 460 V AC 200 A 575 V AC
Poles description	3P
Range of Product	DPS
Thermal overload type	Melting alloy
Number of thermal units required	3

Ordering and shipping details

Category	21381 - 8911 DP
Discount Schedule	CP1
GTIN	00785901192541
Nbr. of units in pkg.	1
Package weight(Lbs)	2.98 Lb(US) (1.352 kg)

Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.30 In (13.462 cm)
Package 1 width	4.80 In (12.192 cm)
Package 1 Length	8.30 In (21.082 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**