

## Product data sheet

### Characteristics

# 8940SSE4050V02S

Pump Panel, NEMA Type S, Well Guard, Size 3, 90A, 5kA SCCR, 50HP, 100A Class H and K fuse clip, Motor Logic SSOLR, 120VAC 60Hz coil, NEMA 3R



Product availability: Stock - Normally stocked in distribution facility

Price\*: 4194.00 USD



### Main

Product name	Well-Guard Control
Device short name	Class 8940 type SS
Device Application	Pumping

### Complementary

Control circuit	Separate control circuit
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	90 A
Number of poles	3
Maximum Horse Power Rating	50 Hp 480 V AC, 3 phase
Permissible voltage	600 V AC
Control type	Selector switch (HAND-OFF-AUTO) Push-button (START)
Disconnecter device type	Fusible disconnect switch
Associated fuse rating	100 A
Fuse type	H or K
Thermal overload type	Motor Logic solid state class 10/20
Protection Type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical Connection	Screw terminal
NEMA size	3
Maximum Height	49.02 In (1245 mm)
Maximum Width	20.55 In (522 mm)
Maximum Depth	10.35 In (263 mm)

## Environment

NEMA Degree of Protection	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product Certifications	UL Listed NEMA

## Ordering and shipping details

Category	21389 - 8940 NSE,NSF
Discount Schedule	CP1
GTIN	00785901353027
Nbr. of units in pkg.	1
Package weight(Lbs)	100 Lb(US) (45.36 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	1.08 Ft (0.330 m)
Package 1 width	1.92 Ft (0.584 m)
Package 1 Length	4.25 Ft (1.295 m)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**