

# Product data sheet

## Characteristics

# 8940SSG4200V02S

Pump Panel, NEMA Type S, Well Guard, Size 5, 270A, 10 kA SSCR, 200 HP, 400A Class H and K fuse clip, Motor Logic SSOLR, 120 VAC 60 Hz coil, NEMA 3R



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 16286.00 USD



### Main

|                    |                    |
|--------------------|--------------------|
| Product name       | Well-Guard Control |
| Device short name  | Class 8940 type SS |
| Device Application | Pumping            |

### Complementary

|                              |  |
|------------------------------|--|
| Control circuit              | Separate control circuit                             |
| [Uc] control circuit voltage | 120 V AC 60 Hz<br>110 V AC 50 Hz                     |
| Line Rated Current           | 270 A  |
| Number of poles              | 3  |
| Maximum Horse Power Rating   | 200 Hp 480 V AC, 3 phase                             |
| Permissible voltage          | 600 V AC   |
| Control type                 | Selector switch HAND-OFF-AUTO)<br>Push-button START) |
| Disconnecter device type     | Fusible disconnect switch                            |
| Associated fuse rating       | 400 A  |
| Fuse type                    | H or K   |
| Thermal overload type        | Motor Logic solid state class 10/20                  |
| Protection Type              | Overload<br>Phase loss<br>Phase unbalance            |
| Device mounting              | Surface  |
| Electrical Connection        | Screw terminal                                       |
| NEMA size                    | 5  |
| Maximum Height               | 74.49 In (1892 mm)                                   |
| Maximum Width                | 23.50 In (597 mm)                                    |
| Maximum Depth                | 17.56 In (446 mm)                                    |

## Environment

|                           |                                       |
|---------------------------|---------------------------------------|
| NEMA Degree of Protection | NEMA 3R                               |
| Enclosure type            | Weatherproof enclosure indoor/outdoor |
| Product Certifications    | UL Listed<br>NEMA                     |

## Ordering and shipping details

|                       |                        |
|-----------------------|------------------------|
| Category              | 21392 - 8940 NSG,XS    |
| Discount Schedule     | CP1                    |
| GTIN                  | 00785901557432         |
| Nbr. of units in pkg. | 1                      |
| Package weight(Lbs)   | 390 Lb(US) (176.90 kg) |
| Returnability         | Yes                    |
| Country of origin     | MX                     |

## Offer Sustainability

|                           |   |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive         | Not compliant   |
| China RoHS Regulation     | <a href="#">China RoHS Declaration</a>  |
| PVC free                  | Yes   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**