

Product data sheet

Characteristics

9001KA22

PUSH BUTTON CONTACT 600VAC 10A 30MM T-K



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 21.50 USD

Main

Device short name	K
Mounting diameter	1.18 In (30 mm)

Complementary

Line Rated Current	10 A
Contact operation	Standard without fingersafe
Electrical connection	Screw terminals binder head

Environment

Product certifications	CE CSA LR24590 class 3211 03 UL listed file E42259 CCN NKCR
------------------------	---

Ordering and shipping details

Category	21434 - 9001 KA CONTACT BLOCKS
Discount Schedule	CS1
GTIN	00785901343899
Nbr. of units in pkg.	1
Package weight(Lbs)	0.96 Oz (27.216 g)
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.54 In (6.452 cm)
Package 1 width	1.00 In (2.54 cm)
Package 1 Length	6.45 In (16.387 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Environmental Disclosure

 [Product Environmental Profile](#)

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty

18 months

Product Life Status : **Commercialised**