

Product data sheet

Characteristics

9050JCK12V20

Timing Relay, Type JCK, plug In, on delay, adjustable time, 0.3 to 30 seconds, 10A, 240 VAC, 120 VAC/110 VDC



Product availability: Stock - Normally stocked in distribution facility

Price*: 78.00 USD



Main

Range of product	9050JCK
Product or component type	Timer
Time delay type	On-delay
Time delay range	0.3...30 s
[Uc] control circuit voltage	120 V AC 110 V DC

Complementary

Hold-in power consumption in VA	2 VA
Line Rated Current	10 A
Switch function	DPDT
Contacts type and composition	2 NO + 2 NC
Contacts material	Silver nickel
Maximum switching voltage	240 V AC
Mounting support	Socket
Pin number	8
Shape of pin	Tubular
Product compatibility	8501NR51 8501NR52

Environment

Product certifications	UL Recognized UL Listed CE
Ambient air temperature for operation	-18...150 °F (-28...66 °C)
Height	2.40 In (61 mm)
Width	1.69 In (43 mm)
Depth	4.09 In (104 mm)

Ordering and shipping details

Category	21651 - 9050 JCK(NOT JCK60, 70) G P TIMERS
Discount Schedule	CP2
GTIN	00785901032557
Nbr. of units in pkg.	1
Package weight(Lbs)	0.27 Lb(US) (0.12 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	2.60 In (6.604 cm)
Package 1 width	4.40 In (11.176 cm)
Package 1 Length	2.00 In (5.080 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**