

# Product data sheet

## Characteristics

# 9050JCK52V20

Timing Relay, Type JCK, plug In, repeat cycle, adjustable time, 0.3 to 30 seconds, 10A, 240 VAC, 120 VAC/110 VDC



Product availability: Stock - Normally stocked in distribution facility

Price\*: 140.00 USD



### Main

Range of product	9050JCK
Product or component type	Timer
Time delay type	Repeat cycle
Time delay range	0.3...30 s
[Uc] control circuit voltage	120 V AC 110 V DC

### Complementary

Hold-in power consumption in VA	2 VA
Line Rated Current	10 A
Switch function	DPDT
Contacts type and composition	2 NO + 2 NC
Contacts material	Silver nickel
Maximum switching voltage	240 V AC
Mounting support	Socket
Pin number	8
Shape of pin	Tubular
Product compatibility	8501NR52 8501NR51

### Environment

Product certifications	CE UL Recognized UL Listed
Ambient air temperature for operation	-18...150 °F (-28...66 °C)
Height	2.40 In (61 mm)
Width	1.69 In (43 mm)
Depth	4.09 In (104 mm)

## Ordering and shipping details

Category	21651 - 9050 JCK(NOT JCK60, 70) G P TIMERS
Discount Schedule	CP2
GTIN	00785901032984
Nbr. of units in pkg.	1
Package weight(Lbs)	0.33 Lb(US) (0.15 kg)
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.00 In (5.08 cm)
Package 1 width	2.60 In (6.604 cm)
Package 1 Length	4.40 In (11.176 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Weight	3.00 Lb(US) (1.361 kg)
Package 2 Height	4.50 In (11.43 cm)
Package 2 width	10.00 In (25.4 cm)
Package 2 Length	11.00 In (27.94 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**