

Product data sheet

Characteristics


9065SDO15

Overload Relay, Type S, melting alloy, replacement overload, NEMA size 4, 3 pole, 3 phase, 135A, 600VAC



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 422.30 USD



Main

Range of product	Replacement Relay
Product destination	Starter
Thermal overload type	Melting alloy

Complementary

NEMA size	4
Phase	3 phase
Number of thermal units required	3
Mounting support	Mounting plate
[Ue] rated operational voltage	600 V AC
Height	6.97 In (177 mm)
Width	5.31 In (134.9 mm)
Depth	5.74 In (145.8 mm)


Ordering and shipping details

Category	21661 - 9065 A,C,F,G,S(NOT SS)
Discount Schedule	CP1
GTIN	00785901850809
Nbr. of units in pkg.	1
Package weight(Lbs)	3.3 Lb(US) (1.50 kg)
Returnability	No
Country of origin	MX

Packing Units

Package 1 Height	6.30 In (16.002 cm)
Package 1 width	6.60 In (16.764 cm)
Package 1 Length	8.50 In (21.590 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**