

# Product data sheet

## Characteristics

# 9070T1500D20

Transformer, Type T, industrial control, 1500 VA,  
208/230/460 VAC primary / 115 VAC secondary,  
1 phase, 50/60 Hz, 55 °C



Product availability: Stock - Normally stocked in distribution facility

Price\*: 1460.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	1500 VA 1500 VA
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	1500 VA UL 1500 VA CSA 1500 VA NOM 1000 VA
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	6.17 In (156.72 mm)
Width	7.06 In (179.32 mm)
Depth	7.17 In (182.12 mm)
Product compatibility	FSC2

### Environment

Product certifications	UL Listed CSA
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

## Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901322290
Nbr. of units in pkg.	1
Package weight(Lbs)	46.1 Lb(US) (20.91 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Package 1 Height	12.30 In (31.242 cm)
Package 1 width	11.70 In (29.718 cm)
Package 1 Length	14.70 In (37.338 cm)

## Offer Sustainability


Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Connections and Wiring Diagrams

Voltage Code	Voltages		Connections	
	Primary	Secondary	Primary	Secondary
D20	208/230/460	115	208: Connect to H1 and H2 230: Connect to H1 and H3 460: Connect to H1 and H4	Connect to X1 and X2



Product Life Status : **Commercialised**