

# Product data sheet

## Characteristics

# 9070T350D23

Transformer, Type T, industrial control, 350 VA, 120/240 VAC primary / 24 VAC secondary, 1 phase, 50/60 Hz, 80 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price\*: 432.00 USD



### Main

Product or component type	Industrial Control Transformer
Rated power in VA	350 VA
Range of product	T

### Complementary

Phase	1 phase
Rated power in VA	350 VA UL 350 VA CSA 350 VA NOM 250 VA
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	3.84 In (97.54 mm)
Width	4.5 In (114.30 mm)
Depth	5.11 In (129.79 mm)
Material	Copper winding
Product compatibility	FSC2

### Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

## Ordering and shipping details

Category	16201 - 9070 T (NOT TF) 250-2000VA
Discount Schedule	CP8
GTIN	00785901907275
Nbr. of units in pkg.	1
Package weight(Lbs)	10.65 Lb(US) (4.831 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.40 In (16.256 cm)
Package 1 width	7.10 In (18.034 cm)
Package 1 Length	7.90 In (20.066 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	10 Years
----------	----------

Product Life Status : **Commercialised**