

Product data sheet

Characteristics

9070T350D3

Transformer, Type T, industrial control, 350 VA,
208 VAC primary / 120 VAC secondary, 1 phase,
50/60 Hz, 80 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price*: 432.00 USD



Main

Product or component type	Industrial Control Transformer
Rated power in VA	350 VA
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	350 VA UL 350 VA CSA 350 VA NOM 250 VA
Temperature rise	80 °C
Electrical connection	Screw clamp terminals
Height	3.84 In (97.54 mm)
Width	4.5 In (114.30 mm)
Depth	5.11 In (129.79 mm)
Material	Copper winding
Product compatibility	FSC2

Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
NEMA degree of protection	Not rated (open device)
Insulation temperature	266 °F (130 °C)

Ordering and shipping details

Category	16206 - 9070 T (NOT TF) MTO
Discount Schedule	CP8
GTIN	00785901322283
Nbr. of units in pkg.	1
Package weight(Lbs)	10.20 Lb(US) (4.627 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.40 In (16.256 cm)
Package 1 width	6.70 In (17.018 cm)
Package 1 Length	7.20 In (18.288 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	10 Years
----------	----------

Product Life Status : **Commercialised**