

Product data sheet

Characteristics

9070T5000D33

Transformer, Type T, industrial control, 5000 VA, 380/400/415 VAC pri / 115/230 VAC sec, 1 phase, 50/60 Hz, 115 °C rise



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 3368.00 USD

Main

Product or component type	Industrial Control Transformer
Rated power in VA	5000 VA
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	8.75 In (222.25 mm)
Width	9 In (228.60 mm)
Depth	9.15 In (232.41 mm)
Product compatibility	FSC2

Environment

Product certifications	UL Listed CUL CSA
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16205 - 9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	00785901334385
Nbr. of units in pkg.	1
Package weight(Lbs)	95.40 Lb(US) (43.273 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	13.20 In (33.528 cm)
Package 1 width	11.80 In (29.972 cm)
Package 1 Length	14.80 In (37.592 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**