

Product data sheet

Characteristics

9070T5000D3

Transformer, Type T, industrial control, 5000 VA,
208 VAC primary / 120 VAC secondary, 1 phase,
50/60 Hz, 115 °C rise



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 3015.00 USD

Main

Product or component type	Industrial Control Transformer
Rated power in VA	5000 VA
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	8.75 In (222.25 mm)
Width	9 In (228.60 mm)
Depth	9.15 In (232.41 mm)
Material	Copper winding
Product compatibility	FSC2

Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16205 - 9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	00785901152200
Nbr. of units in pkg.	1
Package weight(Lbs)	92.3 Lb(US) (41.87 kg)
Returnability	No
Country of origin	US

Packing Units

Package 1 Height	12.50 In (31.750 cm)
Package 1 width	12.38 In (31.445 cm)
Package 1 Length	12.38 In (31.445 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	10 Years
----------	----------

Product Life Status : **Commercialised**