

Product data sheet

Characteristics

9070T750D37

Transformer, Type T, industrial control, 750 VA, 600 VAC primary / 120/240 VAC secondary, 1 phase, 50/60 Hz, 115 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price*: 840.00 USD



Main

Product or component type	Industrial Control Transformer
Rated power in VA	750 VA
Range of product	T

Complementary

Phase	1 phase
Rated power in VA	750 VA UL 750 VA CSA 750 VA NOM 500 VA
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	4.51 In (114.55 mm)
Width	5.25 In (133.35 mm)
Depth	5.61 In (142.49 mm)
Product compatibility	FSC2

Environment

Product certifications	UL Listed CSA
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

Ordering and shipping details

Category	16206 - 9070 T (NOT TF) MTO
Discount Schedule	CP8
GTIN	00785901689218
Nbr. of units in pkg.	1
Package weight(Lbs)	17.00 Lb(US) (7.711 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.80 In (17.272 cm)
Package 1 width	8.20 In (20.828 cm)
Package 1 Length	8.80 In (22.352 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	10 Years
----------	----------

Product Life Status : **Commercialised**