

# Product data sheet

## Characteristics

# 9070TF1000D20

Transformer, Type TF, industrial control, 1000 VA, 208/230/460 VAC pri / 115 VAC second, 1 phase, 50/60 Hz, 115 °C rise



Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 1320.00 USD

### Main

Product or component type	Industrial Control Transformer
Rated power in VA	1000 VA
Primary voltage	208/230/460 V
Secondary voltage	115 V
Range of product	TF

### Complementary

Phase	1 phase
Rated power in VA	1000 VA UL 1000 VA CSA 1000 VA NOM 600 VA
Primary voltage	208/230/460 V 115 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Height	7.46 In (189.48 mm)
Width	7.06 In (179.32 mm)
Depth	5.92 In (150.37 mm)
Material	Copper winding
Product compatibility	FSC2

### Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA degree of protection	Not rated (open device)
Insulation temperature	356 °F (180 °C)

### Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	00785901149019
Nbr. of units in pkg.	1
Package weight(Lbs)	30.90 Lb(US) (14.016 kg)
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 In (27.94 cm)
Package 1 width	11.25 In (28.575 cm)
Package 1 Length	14.19 In (36.043 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**