

Product data sheet

Characteristics

9070TF1500D33

Transformer, Type TF, industrial control, 1500 VA, 380/400/415 VAC pri / 115/230 VAC sec, 1 phase, 50/60 Hz, 115 °C rise



Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 1485.00 USD

Main

Product or Component Type	Industrial Control Transformer
Range of Product	TF

Complementary

Phase	1 phase
Rated power in VA	1500 VA UL 1500 VA CSA 1500 VA NOM 1000 VA
Primary voltage	380/400/415 V 115/230 V
Fuse type	10.3 x 38 mm CC top
Temperature rise	115 °C
Electrical Connection	Screw clamp terminals
Maximum Height	7.46 In (189.48 mm)
Maximum Width	7.06 In (179.32 mm)
Maximum Depth	5.92 In (150.37 mm)
Product Compatibility	FSC2

Environment

Product Certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

Ordering and shipping details

Category	16207 - 9070 TF (NOT T) MTO
Discount Schedule	CP8
GTIN	00785901182726
Nbr. of units in pkg.	1
Package weight(Lbs)	34.40 Lb(US) (15.604 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 In (27.94 cm)
Package 1 width	11.25 In (28.575 cm)
Package 1 Length	14.19 In (36.043 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**