

# Product data sheet

## Characteristics

# 9070TF150D3

Transformer, Type TF, industrial control, 150 VA, 208 VAC primary / 120 VAC secondary, 1 phase, 50/60 Hz, 55 °C rise



Product availability: Stock - Normally stocked in distribution facility

Price\*: 276.00 USD



### Main

Product or Component Type	Industrial Control Transformer
Rated power in VA	150 VA
Primary Voltage	208 V
Secondary Voltage	120 V
Range of Product	TF

### Complementary

Phase	1 phase
Rated power in VA	150 VA
Primary voltage	208 V 120 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	55 °C
Electrical Connection	Screw clamp terminals
Maximum Height	4.5 In (114.30 mm)
Maximum Width	3.75 In (95.25 mm)
Maximum Depth	3.59 In (91.19 mm)
Material	Copper winding
Product Compatibility	FSC1

### Environment

Product Certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
NEMA Degree of Protection	Not rated (open device)
Insulation temperature	221 °F (105 °C)

## Ordering and shipping details

Category	16202 - 9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	00785901905783
Nbr. of units in pkg.	1
Package weight(Lbs)	6.21 Lb(US) (2.817 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.60 In (16.764 cm)
Package 1 width	6.80 In (17.272 cm)
Package 1 Length	7.80 In (19.812 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : **Commercialised**